

AC INDUCTION MOTOR DATA SHEET

Model No.or RFQ No.		Item No.		Rev. No. [0]			
Project Name		Project No.		Quantity sets			
GENERAL SPECIFICATION			PERFORMANCE DATA				
Frame Size	160M		Rated Output	15 kW 20 HP			
Type	HS		Number of Poles	2			
Enclosure(Protection)	Totally Enclosed (IP55)		Rotor Type	Squirrel Cage			
Method of Cooling	IC411(FC)		Starting Method*	☐ D.O.L ☒ Y- Δ			
Rated Frequency	60 Hz		Rated Voltage	440 V	380 V 220 V		
Number of Phases	3		Current	Full Load	25.1 A 29.0 A 50.2 A		
Insulation Class	☒ F ☐ B ☐ H		Locked-rotor**	650 %	650 % 650 %		
Temp. Rise at full load (by resistance method)	at 1.0 S.F 80 deg. C		Efficiency	50% Load 89.7 %			
Motor Location	☒ Indoor ☐ Outdoor			75% Load 90.7 %			
Altitude	Less than 1000 meter			100% Load 90.2 %			
Relative Humidity	Less than 80 %		Power Factor(p.u)	50% Load 0.800			
Ambient Temp.	40 deg. C (Max.)			75% Load 0.857			
Duty Type	Continuos (S1)			100% Load 0.870			
Service Factor	1.15		Speed at Full Load	3535 r.p.m			
Mounting	☐ B3 ☐ B5 ☐ V1 ☒ B3/B5		Torque	Full Load 4.1 kg·m			
Bearing	Type	Anti-Friction		Locked-rotor** 180 %			
	DE/N-DE	6309ZZC3 / 6309ZZC3		Breakdown** 250 %			
	Lubricant	Grease(Polyrex-EM)	Moment of Inertia (J)	Load(Max.) 2.300 kg·m²			
External Thrust	Not applicable			Motor 0.049 kg·m²			
Coupling Method	☒ Direct ☐ V-Belt		Sound Pressure Level (No-load & mean value at 1m from motor)	79 dB(A)			
Shaft Extension	☒ Single ☐ Double		Vibration	2.2 mm/sec (r.m.s)			
Terminal	Main	☐ Steel ☒ Cast Iron	Permissible number of consecutive starts	Cold	3 times		
Box	Aux.	☐ Yes ☒ No		Hot	2 times		
	Location	Refer to Outline Drawing	Paint	Munsell No.	4.0PB5.4/5.5(VL-451)		
Application			SUBMITTAL DRAWING				
Area classification	Non-Hazardous		Outline Dimension Drawing \ Motor Weight(Approx.)				
Type of Ex-Protection	Not applicable		B3 kg				
Applicable Standard	KS,IEC,NEMA MG1 Part30(Vpeak)		B5 kg				
ACCESSORIES			V1 kg				
			B3/B5 227B2040AB05 123 kg				
			Main T-Box Ass'y 227B8008LA1				
SPARE PARTS			REMARK				
			High Efficiency				
			* For use on PWM VFD 10:1VT, 3:1CT@1.0S.F&F Temp. rise				
			Date	DSND	CHKD	CHKD	APPD
			2011-04-14	W.H.BACK	S. J. RA	O. J. KIM	J. H. KIM

Note: Others not mentioned in this data sheet shall be in accordance with maker standard.

Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.

Inspection and performance test shall be maker standard, if not mentioned.

* In case of Inverter-Fed Motor, performance data is based on sine wave tests.


** Data is based on when the motor is supplied at rated voltage & frequency. and the data is expressed as a percentage of full-load value.

HHI W230-131-1 * In case of Inverter or V.V.V.F Motor:Performance data is based on sine wave tests. A4(210mm X 297mm)


Type	:	HS
Full Load Torque	:	4.1 Kg.m
Motor moment of Inertia (J)	:	0.049 Kg.m ²
Load moment of Inertia (J)	:	2.300 Kg.m ²

15 kW		2 P		60 Hz	
Speed at Full Load :				3535 RPM	
Rated Voltage	440V	380V	220V		
Full Load Current	25.1A	29.0A	50.2A		



SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F & CURRENT CURVE



HYUNDAI
HEAVY INDUSTRIES CO., LTD.
Electro-Electric System Division



PT	DESCRIPTION	MATERIAL	DIMENSION	Q'TY
1	CONDUIT BOX	FC15	---	1
2	CONDUIT BOX COVER	FC15	---	1
3	O-RING / COVER	EPDM	φ4	1
4	BOX GASKET	NBR	---	1
5	COVER+BOX HEX BOLT	S45C	M6 X L20	4
6	BOX+FRAME HEX BOLT	S45C	M8 X L20	4
7	GROUND TERMINAL LUG	CU	---	1

REV	DATE	CONTENTS	REV'D BY	CHK'D BY	APP'D BY
1					
2					
3					
4					
5					
6					
7					
8					
9					

Q'TY	DESCRIPTION	MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK	NO.
APP'D BY	KIM.Y.S	UNIT	MM				
CHK'D BY	KO.S.H	SCALE	1:1				
CHK'D BY	---	PROJEC'N	3-4# (3rd Angle)				
DSND BY	Y.J.HWANG	DATE	2005.02.16				
TITLE				REF. NO.	227B8008LA1	Sheet No. of	
TERMINAL BOX ASSEMBLY				DWG NO.	227B8008LA1	Revision No. 0	