

AC INDUCTION MOTOR DATA SHEET

Model No.or RFQ No.		Item No.		Rev. No. [0]			
Project Name		Project No.		Quantity sets			
GENERAL SPECIFICATION			PERFORMANCE DATA				
Frame Size	200L		Rated Output	37 kW 50 HP			
Type	HS		Number of Poles	2			
Enclosure(Protection)	Totally Enclosed (IP55)		Rotor Type	Squirrel Cage			
Method of Cooling	IC411(FC)		Starting Method*	☒ D.O.L ☐ Y- Δ			
Rated Frequency	60 Hz		Rated Voltage	440 V	380 V 220 V		
Number of Phases	3		Current	Full Load	58.4 A 67.6 A 116.8 A		
Insulation Class	☒ F ☐ B ☐ H		Locked-rotor**	650 %	650 % 650 %		
Temp. Rise at full load (by resistance method)			Efficiency				
at 1.0 S.F 80 deg. C			50% Load 91.9 %				
Motor Location	☐ Indoor ☒ Outdoor		75% Load 92.9 %				
Altitude	Less than 1000 meter		100% Load 92.4 %				
Relative Humidity	Less than 80 %		Power Factor(p.u)				
Ambient Temp.	40 deg. C (Max.)		50% Load 0.855				
Duty Type	Continuos (S1)		75% Load 0.890				
Service Factor	1.15		100% Load 0.900				
Mounting	☐ B3 ☐ B5 ☒ V1 ☐ B3/B5		Speed at Full Load 3560 r.p.m				
Bearing	Type	Anti-Friction	Torque				
	DE/N-DE	6212ZC3 / 6211ZC3	Full Load 10.1 kg·m				
	Lubricant	Grease(Gadus S2 V100 2)	Locked-rotor** 160 %				
External Thrust	Not applicable		Breakdown** 230 %				
Coupling Method	☒ Direct ☐ V-Belt		Moment of Inertia (J)				
Shaft Extension	☒ Single ☐ Double		Load(Max.) 4.750 kg·m²				
Terminal	Main	☐ Steel ☒ Cast Iron	Motor 0.168 kg·m²				
Box	Aux.	☐ Yes ☒ No	Sound Pressure Level (No-load & mean value at 1m from motor)				
	Location	Refer to Outline Drawing	86 dB(A)				
Application			Vibration 2.2 mm/sec (r.m.s)				
Area classification	Non-Hazardous		Permissible number of				
Type of Ex-Protection	Not applicable		Cold 3 times				
Applicable Standard	KS,IEC,NEMA MG1 Part30(Vpeak)		Hot 2 times				
ACCESSORIES			Paint	Munsell No.	4.0PB5.4/5.5(VL-451)		
			SUBMITTAL DRAWING				
			Outline Dimension Drawing \ Motor Weight(Approx.)				
			B3		kg		
			B5		kg		
V1	227B1932CB01	327	kg				
B3/B5		kg					
Main T-Box Ass'y			227B8003CB5				
SPARE PARTS			REMARK				
			High Efficiency				
			* For use on PWM VFD 10:1VT, 3:1CT@1.0S.F&F Temp. rise				
			Date	DSND	CHKD	CHKD	APPD
			2011-04-14	W.H.BACK	S. J. RA	O. J. KIM	J. H. KIM

Note: Others not mentioned in this data sheet shall be in accordance with maker standard.

Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.

Inspection and performance test shall be maker standard, if not mentioned.


* In case of Inverter-Fed Motor, performance data is based on sine wave tests.

** Data is based on when the motor is supplied at rated voltage & frequency. and the data is expressed as a percentage of full-load value.


Type	:	HS
Full Load Torque	:	10.1 Kg.m
Motor moment of Inertia (J)	:	0.168 Kg.m ²
Load moment of Inertia (J)	:	4.750 Kg.m ²



37 kW		2 P		60 Hz	
Speed at Full Load :				3560 RPM	
Rated Voltage	440V	380V	220V		
Full Load Current	58.4A	67.6A	116.8A		

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F & CURRENT CURVE





VIEW "A"

NOTE

1.TOLERANCE :

FLANGE HOLES	$\phi 19 \begin{smallmatrix} +0.43 \\ -0 \end{smallmatrix}$
RABBET DIAMETER	$\phi 350 \begin{smallmatrix} +0.016 \\ -0.013 \end{smallmatrix}$
SHAFT DIAMETER	$\phi 55 \begin{smallmatrix} +0.030 \\ +0.011 \end{smallmatrix}$
KEYWAY WIDTH	$16 \begin{smallmatrix} +0 \\ -0.043 \end{smallmatrix}$
KEYWAY DEPTH	$49 \begin{smallmatrix} +0 \\ -0.2 \end{smallmatrix}$



* CAST IRON CONDUIT BOX

APPD BY	KIM Y.S.	UNIT	mm
CHKD BY	LEE K.S.	SCALE	1/10
CHKD BY	KIM I.K.	PROJEC'N	3rd Angle
DSND BY	JANG Y.G.	DATE	2007.12.05

SUBJECT

KS 200L 2P

CAD PROJ \ FILE

XSDNKS\B2060AB09

TITLE

OUTLINE

REF. NO


B2060AB09

Sheet No. of

DWG NO

227B2060AB09

Revision No. 0



PT	DESCRIPTION	MATERIAL	DIMENSION	Q.TY
1	CONDUIT BOX	FC20		1
2	C/B COVER	FC20		1
3	GASKET(COVER)	N.B.R	T2X170X210	1
4	SCREW(COVER)	S45C	M8XL20	4
5	GASKET(C/B)	N.B.R		1
6	SCREW(C/B)	S45C	M8XL20	4
7	TERMINAL LUG	CU	T1.6	
8	TERMINAL GROUND	CU	T1.6	1
9	WASHER	S45C	M8 X L10	4

Q'TY	DESCRIPTION	MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK	NO.
APPD	BY KIM JIN HONG	UNIT	MM				
CHKD	BY KIM YU SUNG	SCALE	1/2				
CHKD	BY GO SECK HAN	PROJEC'T	3 [2]1q12L(3rd				
DSND	BY LEE KWANG SOO	DATE	94.12.20				
				REF. NO.	B8003CB5	Sheet No.	of
				DWG NO.	227B8003CB5	Revision No.	0



CONDUIT BOX
& COVER ASS'Y