




Note: Others not mentioned in this data sheet shall be in accordance with maker standard.
 Above technical data are only design values and shall be guaranteed with tolerance of applicable standard.
 Inspection and performance test shall be maker standard, if not mentioned.
 * In case of Inverter-Fed Motor, performance data is based on sine wave tests.
 ** Data is based on when the motor is supplied at rated voltage & frequency. and the data is expressed as a percentage of full-load value.


Type	:	HS
Full Load Torque	:	30.1 Kg.m
Motor moment of Inertia (J)	:	0.950 Kg.m ²
Load moment of Inertia (J)	:	27.600 Kg.m ²


55 kW		4 P		60 Hz	
Speed at Full Load :				1780 RPM	
Rated Voltage	440V	380V	220V		
Full Load Current	90.2A	104.5A	180.5A		



SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F & CURRENT CURVE







REV	DATE	CONTENTS	REV'D BY	CHK'D BY	Q.P. CHK	APP'D BY
1						

1	EARTH TERMINAL LUG					5
1	CABLE ENTRY PLATE					4
1	GASKET	NBR				3
1	TERMINAL BOX COVER	CAST IRON				2
1	TERMINAL BOX BODY	CAST IRON				1
Q'TY	DESCRIPTION	MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK NO.
APP'D BY	김진오	UNIT	MM			
Q.P. CHK	주영걸	SCALE	NONE			
CHK'D BY	권오철	PROJEC'T	3 2#(3rd Angle)			
DSND BY	김헌태	DATE	92.06.05			
				SUBJECT	H/A6 - 200, 225Fr.	CAD PROJ. & FILE &
				TITLE	(CAST IRON)	T-BOX-M \ 36016881
				REF. NO	3M-016881	Sheet No. of
				DWG NO	3M-016881	Revision No. 0