

Customer :
Project Name :
Project No. :
Revision No. :

SPECIFICATION for INDUCTION MOTOR



Contents


1 . Data Sheet of AC Induction Motor	- 1Sheets
2 . Speed-Torque & Current Curve	- 1Sheets
3 . Outline Dimension Drawing	- 1Sheets
4 . Main Terminal Box Drawing	- 1Sheets

		AC INDUCTION MOTOR DATA SHEET							
Model No.or RFQ No.		3806KSTD40SSDS1STFE3V11DL0SDS		Item No.		Rev. No.		[]	
Project Name				Project No.		Quantity			
GENERAL SPECIFICATION				PERFORMANCE DATA					
Frame Size		80M		Rated Output		0.75 kW		1 HP	
Type		HLP-0.75/4		Number of Poles		4			
Enclosure(Protection)		Totally Enclosed (IP55)		Rotor Type		Squirrel Cage			
Method of Cooling		IC411(FC)		Starting Method*		☒ D.O.L ☐ Y-Δ			
Rated Frequency		60 Hz		Rated Voltage		380 V			
Number of Phases		3		Current		Full Load		1.9 A	
Insulation Class		☒ F ☐ B ☐ H				Locked-rotor**		750 %	
Temp. Rise at full load (by resistance method)				Efficiency					
at 1.0 S.F		80 deg. C				50% Load		76.5 %	
Motor Location		☒ Indoor ☐ Outdoor				75% Load		81.0 %	
Altitude		Less than 1000				100% Load		83.5 %	
Relative Humidity		Less than 80 %		Power Factor(p.u)					
Ambient Temp.		40 deg. C (Max.)				50% Load		0.485	
Duty Type		Continuous(S1)				75% Load		0.610	
Service Factor		1.15				100% Load		0.702	
Mounting		☐ B3 ☐ B5 ☒ V1 ☐ B3/B5		Speed at Full Load		1740 r.p.m			
Bearing		Type		Anti-Friction		Torque			
		DE/N-DE		6204ZZ / 6203ZZ		Full Load		0.4 kg·m	
		Lubricant		Grease(HIFLEX L-3)		Locked-rotor**		260 %	
External Thrust		Not applicable				Breakdown**		300 %	
Coupling Method		☒ Direct ☐ V-Belt		Moment of Inertia (J)					
Shaft Extension		☒ Single ☐ Double				Load(Max.)		0.625 kg·m²	
Terminal Box		Main		☐ Steel ☒ Cast Iron		Motor		0.002 kg·m²	
		Aux.		☐ Yes ☒ No		Sound Pressure Level (No-load & mean value at 1m from motor)			
		Location		Refer to Outline Drawing				64 dB(A)	
Application				Vibration		1.6 mm/sec (r.m.s)			
Area classification		Not applicable		Permissible number of consecutive starts		Cold		3 times	
Type of Ex-Protection		Non-Hazardous				Hot		2 times	
Applicable Standard		KS, IEC, NEMA MG1 Part30(Vpeak)		Paint		Munsell No.		4.4PB5.5/5.6(VL-451)	
ACCESSORIES				SUBMITTAL DRAWING					
				Outline Dimension Drawing		\		Motor Weight(Approx.)	
				V1		LM-A1080V1P1001		14 kg	
				Main T-Box Ass'y		3M-148548			
				REMARK					
				*.Premium Efficiency(IE3)					
				*.For use on PWM VFD 10:1VT,3:1CT@1.0S.F&F Temp.rise					
SPARE PARTS				Date		DSND		CHKD	
				2018-04-25		R.G. KIM		-	
								APPD	
								S.K. HAN	
Note: Others not mentioned in this data sheet shall be in accordance with maker standard. Above technical data are only design values and shall be guaranteed with tolerance of applicable standard. Inspection and performance test shall be maker standard, if not mentioned. * In case of Inverter-Fed Motor, performance data is based on sine wave tests. ** The data are based on rated voltage & frequency, and data are expressed as a percentage of full load value.									


Type :	HLP-0.75/4	
Full Load Torque :	0.4	kg.m
Motor moment of Inertia (J) :	0.002	kg.m ²
Load moment of Inertia (J) :	0.625	kg.m ²


0.75 kW	4 P	60 Hz
Speed at Full Load : 1740 RPM		
Rated Voltage	380V	
Full Load Current	1.9A	

SPEED VS TORQUE & CURRENT CURVE



OUTPUT VS EFF., P.F & CURRENT CURVE





THIS DRAWING IS PROPRIETARY TO HYUNDAI ELECTRIC. NO PART OF THIS DRAWING
MAYBE REPRODUCED WITHOUT THE PERMISSION OF HYUNDAI ELECTRIC.

본 도면은 현대일렉트릭(주) 재산이므로
허가없이 복사할 수 없음 (취급주의)

HYUNDAI
ELECTRIC



SEC. "A" - "A"

▽	50S
▽▽	12.5S
▽▽▽	3.2S
▽▽▽▽	0.4S

REV	DATE	CONTENTS	REVD BY	CHKD BY	CHKD BY	APPD BY

일반가공공차		일반재관공차	
1-4	±0.1	6-30	±0.5
4-18	±0.2	30-120	±0.8
18-63	±0.3	120-315	±1.2
63-250	±0.5	315-1000	±2.0
250-	±0.8	1000-	±3.0

Q'TY	DESCRIPTION		MATERIAL	DIMENSION	WEIGHT	PART NO.	REMARK	NO.
APPD BY	S.K.HAN		UNIT	mm	SUBJECT	FR.71~90 (AL)		DWG SIZE
CHKD BY	S.Y.KIM		SCALE	1/1				A3 (1:1)
CHKD BY	R.G.KIM		PROJEC'N	3각법 (3rd Angle)	TITLE Terminal Box Arrangement			
DSND BY	이혜경 R		DATE	2011-10-26				
					REF. NO	227B1537AA	Sheet No.	of
					DWG NO	3M-148548	Revision No.	2